



415 S Airpark Road
Cottonwood, AZ 86326, USA
Phone: (800) 733-0266
Fax: (928) 649-2306
Email: info@preclaboratories.com

Product Technical Fact Sheet

Product Code: CHL-D500

Product Description: High Level Chlorine Dioxide Test Strips 0-500 ppm

Application:

The 0-500 ppm Chlorine Dioxide test strip is used to detect chlorine dioxide at levels usually associated with use in a disinfection/sanitization application.

Test Range: 0-500 ppm

Test Increments: Color charts calibrated at 0, 10, 25, 50, 100, 250, and 500 ppm

Accuracy: +/- ½ color chart unit

Detection Limit: 5 ppm

Storage Recommendations:

Store in original packaging in a cool (20-30C), dry, place out of direct sunlight.

Shelf-Life: Two years from date of manufacture when stored properly in original packaging.

Interferences: Test strip may react to other oxidizing materials, peracetic acid, peroxide, etc.

Instructions for Use:

1. Using a cup-size sample immerse the test strip for 2 seconds.
2. Remove strip face up. Do not shake off excess water.
3. After 10 seconds, compare pad against color chart. (Note: color on the pad may not be uniform; this is normal.)

Chemistry Behind the Test:

The test pad is treated with a formula consisting of buffers, surfactants, and red-ox indicators. The presence of chlorine dioxide in a sample causes the red-ox indicator in the test pad to develop color. The intensity of the color developed is proportional to the amount of chlorine dioxide present.

Disclaimer:

The chlorine dioxide test strips are not intended for use to diagnose, treat, or monitor any medical condition.